

FLUEPAC®-CF PLUS

Powdered Activated Carbon



Description

FLUEPAC®-CF PLUS is a powdered activated carbon specially formulated with a proprietary ingredient to enhance mercury capture in flue gas treatment applications. FLUEPAC® CF PLUS is specially manufactured to provide effective mercury removal while not adversely impacting the air retention properties of the resultant fly ash.

Specifications

| | |
|---------------------------------------|----------------|
| Moisture, as packed by Weight | 12% (max) |
| Sieve Size by volume (laser analysis) | |
| < 100 US Mesh | 100% (min) |
| < 325 US Mesh | 95% (min) |
| Foam Index(CCC TM99) | 30 drops (max) |

Typical Properties

| | |
|---------------------------|--------------|
| Apparent Density (tamped) | 0.5-0.8 g/cc |
| Ignition Temperature | >400°C |

Added Benefits

Existing combustion or incineration systems can be quickly and inexpensively retrofitted to permit the addition of FLUEPAC®-CF PLUS powdered activated carbon. Operation is simple, reliable, and cost-effective. Utility requirements are low.

Features

| |
|---|
| Consistently low foam index |
| Large number of high energy adsorption pores |
| Good transport pore structure |
| Completely devolatilized bituminous coal-based material |

Applications

FLUEPAC®-CF PLUS is specially designed to enhance mercury capture in flue gas streams while providing the added benefit of continued fly ash sales revenue. FLUEPAC®-CF PLUS is injected directly into the flue gas stream and easily removed by existing particulate control devices.

FLUEPAC®-CF PLUS has been proven to be particularly effective in applications where there are low chlorine levels in the flue gas resulting in the mercury species in the flue gas being predominantly elemental mercury (such as coal-fired boilers burning PRB coals). Elemental mercury is much more difficult to remove with standard activated carbons.

Safety Message

Wet activated carbon preferentially removes oxygen from air. In closed or partially closed containers and vessels, oxygen depletion may reach hazardous levels. If workers are to enter a vessel containing carbon, appropriate sampling and work procedures for potentially low oxygen spaces should be followed, including all applicable Federal and State requirements.

Benefits

| |
|--|
| No negative effect on air retention properties and continued fly ash sales revenue recognition. |
| High adsorption capacity for many pollutants. Effluent mercury levels can be reduced by over 95%. |
| Rapid adsorption kinetics lead to low required contact times. |
| Product has a high ignition temperature which permits use over a wide temperature range. Safe bulk storage. |

FLUEPAC® Patents pending.



Making Water and Air Safer and Cleaner

Calgon Carbon Corporation
P.O. Box 717
Pgh, PA USA 15230-0717
1-800-422-7266
Tel: 1-412-787-6700
Fx: 1-412-787-6713

Chemviron Carbon
European Operations of
Calgon Carbon Corporation
Zoning Industriel C de Feluy
B-7181 Feluy, Belgium
Tel: + 32 (0) 64 51 18 11
Fx: + 32 (0) 64 54 15 91

Calgon Carbon Asia PTE LTD
9 Temasek Boulevard
#08-01A Suntec Tower Two
Singapore 038989
Tel: + 65 6 221 3500
Fx: + 65 6 221 3554

Your local representative

