

OLC 12x40

Coconut Activated Carbon



CALGON CARBON CORPORATION

Test	Specification		Calgon Carbon Test Method
	Min	Max	
IODINE NUMBER, mg/g	1050	-	ASTM D4607
ASH, wt%	-	4.0	ASTM D2866
MOISTURE (AS PACKAGED), wt%	-	5	ASTM D2867
DENSITY (APPARENT), g/cc	0.48	-	ASTM D2854
HARDNESS NUMBER	95	-	ASTM D3802
NSF 61 (PASS/FAIL)	PASS	-	NSF 61
US SIEVE SERIES			ASTM D2862
> 12 US MESH	-	5	
< 40 US MESH	-	4	

Typical Properties:

Safety Message

Wet activated carbon preferentially removes oxygen from air. In closed or partially closed containers and vessels, oxygen depletion may reach hazardous levels. If workers are to enter a vessel containing carbon, appropriate sampling and work procedures for potentially low oxygen spaces should be followed, including all applicable Federal and State requirements.



CALGON CARBON CORPORATION

Calgon Carbon Corporation
P.O. Box 717
Pittsburgh, PA USA 15230-0717
1-800-422-7266
Tel: 1-412-787-6700
Fx: 1-412-787-6713

Making Water and Air Safer and Cleaner

Chemviron Carbon
European Operations of
Calgon Carbon Corporation
Zoning Industriel C de Feluy
B-7181 Feluy, Belgium
Tel: + 32 (0) 64 51 18 11
Fx: + 32 (0) 64 54 15 91

Calgon Carbon Asia PTE LTD
9 Temasek Boulevard
#08-01A Suntec Tower Two
Singapore 038989
Tel: + 65 6 221 3500
Fx: + 65 6 221 3554

Your local representative