

Specification

Test	Min	Max	Calgon Carbon Test Method
IODINE NO., mg/g	800	-	ASTM D 4607
MOISTURE, wt%, as packed	-	8	ASTM D 2867
US SIEVE SERIES			ASTM D 5158
< 100 US MESH	99	-	
< 200 US MESH	95	-	
< 325 US MESH	90	-	

Typical Properties:

This activated carbon product is certified to ANSI/NSF Standard 61 and has a standard maximum use level of 250 mg/l

Safety Message

Wet activated carbon preferentially removes oxygen from air. In closed or partially closed containers and vessels, oxygen depletion may reach hazardous levels. If workers are to enter a vessel containing carbon, appropriate sampling and work procedures for potentially low oxygen spaces should be followed, including all applicable Federal and State requirements.



CALGON CARBON CORPORATION

Making Water and Air Safer and Cleaner

Calgon Carbon Corporation
 P.O. Box 717
 Pittsburgh, PA USA 15230-0717
 1-800-422-7266
 Tel: 1-412-787-6700
 Fx: 1-412-787-6713

Chemviron Carbon
 European Operations of
 Calgon Carbon Corporation
 Zoning Industriel C de Feluy
 B-7181 Feluy, Belgium
 Tel: + 32 (0) 64 51 18 11
 Fx: + 32 (0) 64 54 15 91

Calgon Carbon Asia PTE LTD
 9 Temasek Boulevard
 #08-01A Suntec Tower Two
 Singapore 038989
 Tel: + 65 6 221 3500
 Fx: + 65 6 221 3554

Your local representative